

Data Sheet | Flyscreen Door

Ducato | Boxer | Jumper

DESCRIPTION

Semi-assembled pleated flyscreen door for installation inside sliding side door openings of Ducato, Boxer and Jumper campervans (from 2007 onwards)



OPERATION

Manual step-less adjustment. Closing from right to left (as seen from the inside) for left-hand steered vehicles, optionally from right to left for right-hand steered vehicles.

STANDARD DIMENSIONS (MM)		
	H1	H2
Top guider profile length	.,	1,185
Bottom guider profile length	1,295	1,295
Overall height	1,446	1,731

Disclaimer | The specifications in this data sheet are for information purposes only and may be subject to change without prior notice © Horrex 2021

MATERIAL SPECIFICATIONS

Top guider profile

Extruded aluminium 23.5 x 24.6 mm (WxH) in light grey (± RAL7047) or optional dark grey (± RAL7021) powder coated (conditions apply)

Pull bar

Extruded aluminium 50 x 17 mm (WxH) in light grey (± RAL7047) or optional dark grey (± RAL7021) powder coating (conditions apply)

Bottom guiding profile

Extruded anodized aluminium 35.5 x 21.5 mm (WxH)

Side panel (optional)

Black ABS panel, straight for customisation or pre-shaped, aligned with the bodywork and/or interior of the van, for effective protection against insects (conditions apply)

Corner pieces and caps

Colour coordinated injection moulded parts in PA6 and PA6.6

Insect screen mesh

Single pleat black polyester mesh 1.3 x 1.3 mm (mesh opening), optional FR in accordance with standard FMVSS/CMVSS 302 (conditions apply)

INSTALLATION

On-face fixation on the inside with 4 clips underneath the door rubber at the top and 4 screws at the bottom. The required mounting space between door rubber and top cabinet is 27 mm and between sliding door and kitchen cabinet is 20 mm

CI FANING

A soft damp cloth with mild detergent

PACKAGING

Individually or bulk with mounting set





SPECIAL NOTE

Combine a flyscreen door with genuine Horrex rear screen and UCS combi-blinds for a total insect screen solution





